

MACHINES MULTITACHES **MAZAK INTEGREX i-450 H ST**

CN : SMOOTH AI

ANNÉE : 2021

N° SÉRIE : 323070



CARACTÉRISTIQUES TECHNIQUES

Course axe X	695 mm
Course axe Y	300 mm
Course axe Z	1585 mm
Vitesse de broche	5000 tr/min
Vitesse broche secondaire	3300 tr/min
Vitesse broche de fraisage	10 000 tr/min
Passage en BROCHE 1	102 mm
Magasin	74 outils CAPTO C 6

OPTIONS

- Chuck kitagawa BB 212 and B-210 X
- 74 tool CAPTO C6
- Robot interface (advance/Ethernet/ip)
- Automatic front door
- C axis positionning 0.0001 ° contouring / synchronise
- Overload detection system
- Preparation for RMP Probe RENISHAW
- Grundfos 30 bars through mill spindle
- Grundfos 15 bars for coolant through Main spindle and Sub Spindle
- Conveyor MAYFRAN MT 10
- NC CONTROLER
- NO066 Smooth synchronised tapping (milling spindle)
- NO599 B Cylindral and polar co-ordinate
- XX006 MAZAK API
- XX007 G00 Sloope constant
- XX 008 5 Axis machining package for SMOOTH AI
- XX009 Preparation for Multi and Flash tooling system
- XX013 2 additional M code
- XX017 MT connect adaptater



ROBOT YASKAWA
MOTOMAN
ES 165-D-100



